


DAX 120 P

Monofacial Module P-Type PERC

455-465W
Power

21,49%
Maximum Efficiency



HIGHER POWER OUTPUT

Highest Performance and efficiency on the market



TECHNOLOGY

P-Type PERC



MECHANICAL LOAD

5400 Pa Front / 2400 Pa Back



FIRE CLASS

Class 1 UNI 9177



ENVIRONMENT CONDITION

Resistant to harsh environments



POWER CLASS

0+4,99 Watt Positive Tolerance



WARRANTY

20 years product warranty
30 years linear power output warranty

20 YEARS
PRODUCT
WARRANTY

30 YEARS
LINEAR
POWER
OUTPUT
WARRANTY

Certifications

IEC 61215:2021 - IEC 61730:2023

ISO 9001:2015 - ISO 14001:2015 - ISO 45001:2018



IEC 62716
AMMONIA
RESISTANCE



IEC 60068
DUST AND
SAND



IEC 62804
PID



IEC 61701
SALT MIST




daxsolar.it/en

	DAX 120 P10 455		DAX 120 P10 460		DAX 120 P10 465	
	STC	NMOT	STC	NMOT	STC	NMOT
Maximum power - Wp [W]	455	367	460	371	465	375
Maximum power voltage - Vmp [V]	35,11	33,44	35,35	33,65	35,59	33,83
Maximum power current - Imp [A]	12,96	10,80	13,02	10,85	13,07	10,89
Open circuit voltage - Voc [V]	41,43	39,46	41,60	39,62	41,75	39,76
Short circuit current - Isc [A]	13,65	11,38	13,71	11,43	13,76	11,47
Module efficiency - [%]	21,03		21,26		21,49	
Power class - [W]	-0 + 4,99					
Maximum system voltage - [V]	1500 DC					
Maximum series fuse rating - [A]	30					

STC VALUE: 1000 W/m², AM 1.5, temperature 25 °C. | NMOT: 800 W/m², AM 1.5, temperature 20 °C, wind speed 1 m/s, tolerance +/-3 %

Mechanical parameter	
Module dimension	1908 x 1134 x 30 (35*) mm
Weight	23 kg
Solar cells technology	P-Type PERC M10
No. of cells	120 half cut
Glass	32 mm High Transmission, AR Coated Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Junction box	IP68 3 bypass diodes
Connector	MC4 or compatible
Output cable length	1000 mm**
Cable size	4 mm ²
Mechanical load	5400 / 2400 Pa
Safety class	Class II

*On Request | **Customizable on request



Temperature coefficient	
Temperature coefficient at PMax	-0,38 %/°C
Temperature coefficient at Voc	-0,36 %/°C
Temperature coefficient at Isc	+0,07 %/°C
Operational Temperature	-40 / +85 °C
NMOT	44 ±2 °C

Packaging configuration	
Pallet dimension	1920 x 1140 x 1200 mm
Pallet weight	840
Pcs per pallet	36 pz
Pallet per truck	26 pz
Pallet per container	24 pz

Please read the product assembly and safety manual before installation. Specifications in this data sheet are subject to change without notice.

DAX Solar S.r.l.

Legal Headquarters
V.le Bianca Maria, 24
20129 Milano (MI) - IT

Administrative Headquarters
Via Archimede, 45/47
20864 Agrate Brianza (MB) - IT
T +39 039 9468591

Production Headquarters
Via Salaria per L'Aquila, 34
02015 Cittaducale (RI) - IT
T +39 0746 1766636

DAX SOLAR

info@daxsolar.it daxsolar.it/en